



Technical Data Sheet

FEATHERING PROPELLER GREASE

Product Overview

Salt resistance grease is premium semi synthetic water proof grease designed specifically for slow to medium speed plain and anti-friction bearing applications in marine and other hostile environments. Whilst it has found many uses for off road vehicles, due to its exceptionally high base fluid viscosity it is not recommended for normal highway use in automotive wheel and trailer hub bearings

Feature and Benefits

- Waterproof in both salt and fresh water
- Good sealing properties to resist ingress of dirt and moisture.
- High load carrying capability
- Reduces friction and wear
- Highly adhesive to resist vibration and shock

Typical Applications

- Boat Prop Shafts
- Pumps
- Bearings
- Not for automotive use.

Directions for Storage and Use

Product is to be stored in a clean, dry, storage area in its original sealed packaging.

Shelf Life (unopened) – 3 years approx *

*Some bleeding may occur, thorough mixing will homogenise the mixture to its original state.

Product can be applied by brush, applicator or automatic lubrication system. Do not over lubricate.

Do not mix with other lubricants if compatibility is not known, for best results purge system of other lubricants. Apply to clean, dry parts only

Disclaimer

The data sheet is based on personal knowledge and experience and is given as a guideline to its possible uses. It does not take into account variables or conditions out of our control that can affect our product in any way. It is the users' sole responsibility to ensure that the product is suitable for the purpose for which it is being used and this data does not in any way form a warranty. If you are unsure of its suitability please contact us and we will be happy to discuss your needs and supply a sample for testing if required. New Tech Lubes Ltd is committed to supplying the best products and may therefore change the information in this specification at any time.

Available Sizes
400g Cartridge
5kg Tube
12.5kg Pail
25kg Pail
50kg Pail
180kg Barrel

Available Grades
NLGI 1, 0, 00

Physical Characteristics	
Appearance	Green Adhesive grease
Worked Penetration (IP 50)	265 to 295
Operating temperature range	0°C to + 140°C
Dropping point (IP 132) °C	180 min
Timken O.K. load (IP 326)	Kg 25
SKF EMCOR with synthetic salt water	0.1
Water Resistance (DIN 51807)	Fully Resistant
Base fluid viscosity (IP 71) cSt. @ 40°C	1000

